

# TURTLES IN TIME™

TEENAGE MUTANT NINJA TURTLES® © Mirage Studios, USA  
All rights reserved. Trademark use granted to Konami  
under license from Mirage Studios, USA  
TURTLES IN TIME™ is a trademark of Konami Inc.  
© Konami Inc. 1991 Konami® is a trademark of Konami Co., Ltd.

Service #

## 708-215-5100

Jerry Korbecki ext. 122

# INSTRUCTION MANUAL

 **KONAMI®** is a trademark of Konami Industry Co., Ltd.

# T.M.N.T. II PARTS LIST

| <b>Part #</b> | <b>Description</b>                  |
|---------------|-------------------------------------|
| 063003        | T.M.N.T. II P.C.B.                  |
| 063100        | T.M.N.T. II C.P.O.                  |
| 063101        | T.M.N.T. II Player Instruction      |
| 063200        | T.M.N.T. II Marquee                 |
| 063300        | T.M.N.T. II Upper Right Side Decal  |
| 063301        | T.M.N.T. II Upper Left Side Decal   |
| 063302        | T.M.N.T. II Middle Right Side Decal |
| 063303        | T.M.N.T. II Middle Left Side Decal  |
| 063304        | T.M.N.T. II Lower Right Side Decal  |
| 063305        | T.M.N.T. II Lower Left Side Decal   |
| 063306        | T.M.N.T. II P.O.P. Advertiser       |
| 063400        | T.M.N.T. II Manual (4P)             |
| 40905         | 3 & 4 Player Harness                |
| 40901         | Speaker Harness                     |
| 40605         | FCC Cage                            |
| 40615         | Kit Box                             |
| # N/A         | Red Joy Stick (Microswitch)         |
| # N/A         | Blue Joy Stick (Microswitch)        |
| # N/A         | Violet Joy Stick (Microswitch)      |
| # N/A         | Orange Joy Stick (Microswitch)      |
| 30263         | Red Jump Button                     |
| 30264         | Red Attack Button                   |
| 30265         | Blue Jump Button                    |
| 30266         | Blue Attack Button                  |
| 30269         | Violet Jump Button                  |
| 30270         | Violet Attack Button                |
| 30267         | Orange Jump Button                  |
| 30268         | Orange Attack Button                |
| 30261         | Microswitch                         |
| 30262         | Palnut (Plastic)                    |

# PUTTING YOUR BEST GAME FORWARD

## PREPARATION:

For best results, all old graphics should be removed completely from the cabinet. "Stick-on" graphics can be removed by using a hairdryer or hot air device. The heat from the dryer will loosen the adhesive, allowing you to easily peel them off—any adhesive residue can be cleaned off with acetone and a soft dry cloth. (DO NOT USE ACETONE ON SURFACES PAINTED WITH FLAT PAINT.)

## TOOLS YOU NEED:

1. Foaming Aerosol (such as "Windex").
2. Soft Squeegee.
3. X-Acto Knife.

## SIDE PANEL DECALS

1. Spray area of cabinet where Side Panel decals are to be applied with foaming aerosol or a mild soap solution.
2. Remove protective backing from decals.
3. Position decals into place.
4. With a soft squeegee, beginning from the center of the decal, slowly and evenly press out excess foam until you achieve a smooth finish.
5. Allow to set approximately 2 to 3 hours before handling. Maximum adherence is achieved in 48 to 72 hours.

6. Trim side decal to fit your cabinet.

## CONTROL PANEL OVERLAY:

1. Drill any new holes needed.
2. Plug any holes that will not be used. (A permanent epoxy-filler works well for this step.)
3. Pre-position the overlay prior to removing the backing.
4. Slowly apply the overlay—inch by inch on the control panel, removing the backing as you apply it.
5. Once it's in place, by using an X-Acto knife, cut around the button and joystick placements.

## INSTRUCTION/BUTTON DECALS:

Apply the Player Instruction, Button and 1 Player/2 Player decals in their respective positions. Apply pressure liberally. Allow to set as long as possible before putting game on location.

**NOTE:** Maximum adherence is achieved in 48 to 72 hours.

## MARQUEE

(WEAR PROTECTIVE GLASSES WHILE TRIMMING MARQUEE)


1/8" Acrylic Marquee should be cut to fit your game. DO NOT remove protective mask until this is done.

One way of cutting your Marquee is as follows: (Be sure to protect painted side of Marquee from any surface which may scratch or mar finish).


### CUTTING WITH A KNIFE OR SCRIBER:

Acrylic sheet up to 3/16" thick may be cut by a method similar to that used for cutting window glass. Use a scribe of some kind—a scribing knife such as the one pictured, a metal scribe, an awl, or even a sturdy craft knife—to score the sheet. Draw the scribe several times (7 or 8 times for a 3/16" thick piece) along a straight edge held firmly in place. It is best not to remove the protective masking. Make the cuts carefully using firm, even pressure. For best results make each stroke cleanly off the edge of the sheet.

Then clamp the acrylic sheet or hold it rigidly under a straight edge with the scribe mark hanging just over the edge of a table. Protect your hands with a cloth, and apply a sharp downward pressure to the other side of the sheet. It will break along the scratch. Scrape the edges to smooth any sharp corners. This method is not recommended for long breaks or thick material.



Always draw the scribing knife along a straight edge.



Break sheet over edge of table after scribing.

## P.C.B. CAGE INSTALLATION

Konami, Inc. now supplies a new style P.C.B. cage which is superior to old style cages because of ease of installation. The cage is made of a 32 point stem-stock which is fire retardant.

### TO INSTALL THE CAGE:


1. Open cage bottom and secure to desired P.C.B. position.
2. Install printed circuit board inside cage using wood screws, screwed through the cage bottom into cabinet side.
3. Close the cage over printed circuit board and secure with latch on cage.

# T.M.N.T. II TECHNICAL INFORMATION

T.M.N.T. II requires horizontally mounted monitor. It also generates composite negative sync. If your monitor is composite positive sync, you will have to change to composite negative sync.

To alternate composite positive sync to composite negative sync, use 7404 IC or 74LS04 IC. The signal on the output pin from the P.C.B. is a combination of H-sync and V-sync.

**NOTE:** Please refer to Figure 2.



## TROUBLE SHOOTING GUIDE

| PROBLEM:                                                            | POSSIBLE SOLUTION                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No Screen or Constant Reset                                         | <ol style="list-style-type: none"> <li>1). Check +5V line at the P.C.B. Adjust if necessary.</li> <li>2). Make sure all socketed eproms and custom IC's are seated securely. Apply light pressure to secure.</li> <li>3). Check harness to be sure it is not on backwards.</li> </ol>                                                                   |
| No Sound                                                            | <ol style="list-style-type: none"> <li>1). Check +12V line at the P.C.B.</li> <li>2). Make sure both speaker out wires are connected to the speakers. (DO NOT CONNECT A GROUND.)</li> </ol>                                                                                                                                                             |
| Distorted Sound                                                     | <ol style="list-style-type: none"> <li>1). Replace cabinet speaker.</li> </ol>                                                                                                                                                                                                                                                                          |
| I/O Problem (coin 1 doesn't work or Joystick Up doesn't work, etc.) | <ol style="list-style-type: none"> <li>1). Do not hook a coin counter to the coin 1 or coin 2 outputs. This will cause damage.</li> <li>2). Check your schematic for the 74LS253 IC that corresponds to your I/O problem. Check the appropriate pin with a scope or multimeter for a high output (5V), if output is low replace the 74LS253.</li> </ol> |

## CAUTION

DO NOT WIRE COIN COUNTERS TO THE COIN 1 OR COIN 2 OUTPUTS. THIS WILL CAUSE DAMAGE TO THE I/O MICROCHIP 74LS253. COIN COUNTERS CAN ONLY BE WIRED TO COIN COUNTER OUTPUTS.

# T.M.N.T. II MONITOR INFORMATION

## SERVICE INSTRUCTIONS

**NOTE:** All monitors are equipped with automatic degaussing coils (L701) which demagnetize the picture tube every time the monitor is turned on after being off for a minimum of 5 minutes. Should any part of the chassis become magnetized it will be necessary to degauss the affected area with a manual degaussing coil. Move the coil slowly around the CRT face and all surrounding metal parts. Then slowly withdraw for a distance of 6 feet before turning off.

### 1.0 BLACK LEVEL CONTROL ADJUSTMENT

This control has been set at the factory and should not need further attention, however, when the game is connected a slight adjustment of VR201 may be necessary to obtain the proper black level (the black portion of the picture just extinguished).

### 2.0 VERTICAL SIZE (HEIGHT)

Location of this control is shown in Fig. 1. This control must be adjusted slowly, if necessary, until the picture or test pattern attains the correct vertical proportions.

### 3.0 CIRCUIT PROTECTION

A 4.0A pigtail fuse, mounted on the Main Board has been provided to protect the Power Output Circuit.

### 4.0 FOCUS

Adjust the focus control, located on the HV unit (T352), for maximum over-all definition and fine picture detail.

### 5.0 HORIZONTAL HOLD CONTROL ADJUSTMENT, VR351 (See Fig. 1)

A warm-up period of at least five minutes should be allowed before alignment is carried out. With the monitor being driven from the game signal, short TP601 to TP31. Adjust VR351 until the picture stops sliding horizontally. Remove the short.

### 6.0 HORIZONTAL VIDEO POSITION

If the video is off center on the raster some compensation can be made by adjusting this control.

### 7.0 VERTICAL RASTER POSITION ADJUSTMENT

If the video is off center vertically, (short dimension of picture tube) some compensation can be made by moving the vertical raster position adjustment jumper to either positions "U" or "D".


### 8.0 HORIZONTAL RASTER POSITION ADJUSTMENT

If the video is off center horizontally (long dimension of the picture tube) some compensation can be made by moving the horizontal raster position adjustment jumper to either positions "R" or "L".

### 9.0 HORIZONTAL WIDTH ADJUSTMENT

The horizontal width coil is a hexagonal tuning tool adjustment. This control must be adjusted slowly, if necessary, until the picture or test pattern attains the correct horizontal proportions.

\* KONAMI GAMES ARE ALL NEGATIVE COMPOSITE SYNC. USE THE THREE PIN CONNECTOR ON THE MONITOR.



# T.M.N.T. II TECHNICAL INFORMATION

---

## TECHNICAL INFORMATION

---

- (1) Required power capacity  
GND-Vcc 5V 4A or more  
GND-(+12V)  
\*See the Wiring Diagram.
- (2) Output  
R (red) analog, positive  
G (green) analog, positive  
B (blue) analog, positive  
SYNC. H-V complexed, negative
- (3) The monitor should be horizontally installed.
- (4) Use the volume knob on the PCB to adjust sound level.  
Turn the knob clockwise for increased volume. In monaural output mode, use the left volume knob.
- (5) Handle with care.

---

## PLAY INSTRUCTION

---

- 1 to 4 players can play at the same time.
- Choose the character you want to control out of the four individual Ninja Turtles: LEONARDO (Weapon: Katana), MICHAELANGELO (Nunchaku), DONATELLA (Bo staff), or Raphael (pair of sai).
- Deposit coins into the coin slot of the character you want and press ATTACK or JUMP button to start.
- Control your character's movement using the 8-way joystick and attack enemies with ATTACK button. Press ATTACK button repeatedly to slice, slash, hurl, kick, thrust the enemies. Use JUMP button to avoid enemy attack or defeat enemies in the air. Pressing JUMP button longer makes higher jump.
- Press ATTACK and JUMP buttons simultaneously for a powerful Special Attack according to the individuality of each character.
- Press JUMP button while in the air for a flying kick or slash.
- Keep pressing JOYSTICK to run left or right. Press ATTACK button while running to tackle enemies or make a sliding attack.
- Pick up a piece of pizza to fully restore your energy or to make a revolving attack.
- Your energy will be consumed when attacked by enemies. When it is used up, you will lose one life. The game is over when you have lost all the lives.
- There are 9 stages in all. You can continue the game as many times as you want. Any player can join at any time.

---

## CABINET INFORMATION

---

- (1) Use a multi control upright cabinet with four sets of an 8-way joystick and two function buttons.
- (2) Four independent coin slots are necessary. Start buttons are substituted by the function buttons for each player.



8-WAY  
JOYSTICK



ATTACK  
BUTTON



JUMP  
BUTTON

# T.M.N.T. II TECHNICAL INFORMATION (cont.)

---

## SELF TEST

---

Normal: "OK" will be displayed. Then the game will start.

Abnormal: "BAD" will be displayed and self test will repeat. If "15B BAD" is displayed, switch off and switch on again with TEST SWITCH (on the PCB) pressed.

---

## MANUAL TEST

---

### (1) HOW TO START

After switching on the power, press the TEST SWITCH on the PCB or on the cabinet, and you will get the MAIN MENU of the Manual Test.

NOTE: Switching on with TEST SWITCH pressed causes the program in the EEPROM to be initialized to default.

### (2) HOW TO RETURN TO THE GAME MODE

Select "GAME MODE" on the MAIN MENU then press player 1 ATTACK button to return to the game mode.

### (3) ITEMS AND HOW TO SELECT

Use player 1 JOYSTICK to move arrow to desired test and press 1 ATTACK button to initiate testing. Press player 1 ATTACK button during or at the end of each test to return to the MAIN MENU.

I/O CHECK  
SCREEN CHECK  
COLOR CHECK  
SOUND CHECK  
MASK ROM CHECK  
GAME OPTIONS  
COIN OPTIONS  
GAME MODE

1PLYR JOYSTICK = SELECT ITEM  
1PLYR ATTACK = DO CHECK

### (4) EXPLANATION OF THE ITEMS

#### 1. I/O CHECK

Check all the joysticks and buttons to see "1" when switched on. Press player 1 and 2 ATTACK buttons at the same time to return to MAIN MENU.

#### 2. SCREEN CHECK

Adjust focus, alignment, size, etc. using the cross-hatch screen.

#### 3. COLOR CHECK

Adjust color brightness so that the specified area will be colorless.

#### 4. SOUND CHECK

When "SOUND SCALE CHECK" is selected, a music scale sounds. At "SOUND CODE," push player 1 JOYSTICK right/left to change sound code.

#### 5. MASK ROM CHECK

Roms will be checked one after another, and the message "OK" or "BAD" will be displayed on the screen.

#### 6. GAME OPTIONS

Following screen will appear. Use player 1 JOYSTICK up/down to select the item and push JOYSTICK right/left to modify setting. Factory settings are shown in green, and modified results in red. (Settings below are not always the factory settings.)

# T.M.N.T. II TECHNICAL INFORMATION (cont.)

After modification is completed, select "SAVE AND EXIT" and press player 1 ATTACK button to save and return to MAIN MENU.

| GAME OPTIONS                             |                      |
|------------------------------------------|----------------------|
| PLAYER'S LIFE                            | 1 CREDIT 2 LIVES     |
| DIFFICULTY LEVEL                         | 2/MEDIUM             |
| VIDEO SCREEN FLIP                        | NORMAL               |
| SOUND OUTPUT                             | MONAURAL             |
| SOUND IN ATTRACT MODE                    | ON                   |
| LOOP SETTING                             | GAME LOOPS ENDLESSLY |
| FACTORY SETTINGS                         |                      |
| SAVE AND EXIT                            |                      |
| EXIT                                     |                      |
| 1PLYR JOYSTICK UP/DOWN=SELECT OPTION     |                      |
| 1PLYR JOYSTICK RIGHT/LEFT=MODIFY SETTING |                      |

- ...Select from 1 to 8 lives.
- ...Select out of 4 levels.
- ... "NORMAL" or "UPSIDE DOWN"
- ... "STEREO" or "MONAURAL"
- ... "ON" or "OFF"
- ... "GAME OVER AFTER FINAL STAGE" or "GAME LOOPS ENDLESSLY"
- ... All the settings return to default.
- ... Save the modified settings.

\*If you select "EXIT" instead of "SAVE AND EXIT" after modifying some settings, the message appears: "YOU DID NOT SAVE. DO YOU WANT TO SAVE? YES/NO." When you choose "YES," the screen shows "NOW SAVING" and returns to MAIN MENU. If you select "NO," "NO MODIFICATION" is shown and then MAIN MENU appears.

## (7) COIN OPTIONS

Selecting this item, the screen shows following options.

| COIN OPTIONS                             |                  |
|------------------------------------------|------------------|
| PREMIUM START                            | YES 1            |
| STARTING                                 | 2 COINS 1 CREDIT |
| CONTINUATION                             | 1 COIN 1 CREDIT  |
| FACTORY SETTINGS                         |                  |
| SAVE AND EXIT                            |                  |
| EXIT                                     |                  |
| 1PLYR JOYSTICK UP/DOWN=SELECT OPTION     |                  |
| 1PLYR JOYSTICK RIGHT/LEFT=MODIFY SETTING |                  |

- ... "NO" or "YES 1" to "YES 3"
- (The number means the EXTRA coins necessary)

} Same as above "GAME OPTIONS"

When you want "PREMIUM START" setting, choose the number of extra coins necessary for starting, then decide the coin setting for continuation. The number of coins for starting will be the sum of both numbers. If you do not want premium start setting, the number of coins necessary for starting and continuation will be the same.

## \*COIN SETTING OPTIONS

|           |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
|-----------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Coin(s)   | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 2 | 2 | 2 | 3 | 3 | 3 | 4 | 4 | 4 |
| Credit(s) | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 1 | 3 | 5 | 1 | 2 | 4 | 1 | 3 | 5 |



# T.M.N.T. II SUB HARNESS FOR 3 PLAYERS & 4 PLAYERS

|                                            |    |           |              |
|--------------------------------------------|----|-----------|--------------|
| <b>CN3</b><br><b>3P</b><br><b>CONTROLS</b> | 1  | Coin 3    | Blue/White   |
|                                            | 2  | Empty     |              |
|                                            | 3  | 3P Left   | White/Red    |
|                                            | 4  | 3P Right  | White/Yellow |
|                                            | 5  | 3P Up     | White/Black  |
|                                            | 6  | 3P Down   | White/Blue   |
|                                            | 7  | 3P Jump   | White/Brown  |
|                                            | 8  | 3P Attack | White/Orange |
|                                            | 9  | Empty     |              |
|                                            | 10 | Empty     |              |
|                                            | 11 | Empty     |              |
|                                            | 12 | Empty     |              |
|                                            | 13 | Empty     |              |
|                                            | 14 | Empty     |              |
|                                            | 15 | Ground    | Black        |

|                                            |    |           |              |
|--------------------------------------------|----|-----------|--------------|
| <b>CN4</b><br><b>4P</b><br><b>CONTROLS</b> | 1  | Coin 4    | Red/Green    |
|                                            | 2  | Empty     |              |
|                                            | 3  | 4P Left   | Yellow/Black |
|                                            | 4  | 4P Right  | Brown/Black  |
|                                            | 5  | 4P Up     | Green/Yellow |
|                                            | 6  | 4P Down   | Yellow/Red   |
|                                            | 7  | 4P Jump   | Yellow/White |
|                                            | 8  | 4P Attack | Yellow/Blue  |
|                                            | 9  | Empty     |              |
|                                            | 10 | Empty     |              |
|                                            | 11 | Empty     |              |
|                                            | 12 | Empty     |              |
|                                            | 13 | Empty     |              |
|                                            | 14 | Empty     |              |
|                                            | 15 | Ground    | Black        |












# T.M.N.T. II WIRING HARNESS

\*JAMMA HARNESS NOT SUPPLIED

Solder Side ← → Parts Side

|             |   |    |              |
|-------------|---|----|--------------|
| GND         | A | 1  | GND          |
| GND         | B | 2  | GND          |
| +5V DC      | C | 3  | +5V DC       |
| +5V DC      | D | 4  | +5V DC       |
| NOT USED    | E | 5  | NOT USED     |
| +12V DC     | F | 6  | +12V DC      |
| *KEY        | H | 7  | *KEY         |
| (EMPTY)     | J | 8  | COIN COUNTER |
| (EMPTY)     | K | 9  | (EMPTY)      |
| SPEAKER (-) | L | 10 | SPEAKER (+)  |
| (EMPTY)     | M | 11 | (EMPTY)      |
| VIDEO GREEN | N | 12 | VIDEO RED    |
| VIDEO SYNC  | P | 13 | VIDEO BLUE   |
| (EMPTY)     | R | 14 | VIDEO GROUND |
| (EMPTY)     | S | 15 | TEST SWITCH  |
| COIN 2      | T | 16 | COIN 1       |
| NOT USED    | U | 17 | NOT USED     |
| 2P UP       | V | 18 | 1P UP        |
| 2P DOWN     | W | 19 | 1P DOWN      |
| 2P LEFT     | X | 20 | 1P LEFT      |
| 2P RIGHT    | Y | 21 | 1P RIGHT     |
| 2P ATTACK   | Z | 22 | 1P ATTACK    |
| 2P JUMP     | a | 23 | 1P JUMP      |
| NOT USED    | b | 24 | NOT USED     |
| NOT USED    | c | 25 | NOT USED     |
| NOT USED    | d | 26 | NOT USED     |
| GND         | e | 27 | GND          |
| GND         | f | 28 | GND          |

(BASE COLOR/LINE COLOR)



**KONAMI** PWB352359C

MADE IN JAPAN

# CONTROL PANEL DRILLING TEMPLATE


---

Use this Template for All 4 Players Controls


Player 1 Blue  
Player 2 Orange  
Player 3 Purple  
Player 4 Red




JOYSTICK




JUMP



ATTACK





**ATTACK**

**JUMP**

**ATTACK**

**JUMP**


**ATTACK**

**JUMP**


**ATTACK**

**JUMP**

## HOW TO PLAY



### CONTROL



**JUMP**



**ATTACK**


- Each Turtle has a different attack method.
- Press **JUMP** & **ATTACK** buttons at the same time for **SPECIAL ATTACK** !
- Press **JUMP** button longer to jump higher.
- Press **ATTACK** button while jumping for a flying kick or weapon attack.
- Press **ATTACK** button while running to tackle enemies or make sliding attack.
- Pick up pizza for more energy or to make a revolving attack.
- Hit button and wiggle the joystick to escape when caught by enemies.

INSERT MORE COINS TO CONTINUE !


# 063101

THIS EQUIPMENT COMPLIES WITH THE REQUIREMENTS IN PART 15 OF FCC RULES FOR A CLASS A COMPUTING DEVICE. OPERATION OF THIS EQUIPMENT IN A RESIDENTIAL AREA MAY CAUSE UNACCEPTABLE INTERFERENCE TO RADIO & TV RECEPTION REQUIRING THE OPERATOR TO TAKE WHATEVER STEPS NECESSARY TO CORRECT THE INTERFERENCE.

## HOW TO PLAY



### CONTROL



**JUMP**



**ATTACK**


- Each Turtle has a different attack method.
- Press **JUMP** & **ATTACK** buttons at the same time for **SPECIAL ATTACK** !
- Press **JUMP** button longer to jump higher.
- Press **ATTACK** button while jumping for a flying kick or weapon attack.
- Press **ATTACK** button while running to tackle enemies or make sliding attack.
- Pick up pizza for more energy or to make a revolving attack.
- Hit button and wiggle the joystick to escape when caught by enemies.

INSERT MORE COINS TO CONTINUE !


# WIRING DIAGRAM

**NOTICE TO ALL PERSONS RECEIVING THIS DRAWING**  
 PROPRIETARY AND CONFIDENTIAL. Reproduction, forbidden, without the specific written permission of Konami Co., Ltd., 7-3-2 Minatogamine-Hakomachi, Chou-ku, Kobe 650, Japan. This drawing is only conditionally issued. Neither receipt nor possession of this drawing or any operating manual relating to Konami's games or products containing this drawing confers or transfers any right in or license to use the printed circuit boards relating to this drawing or other subject matter of the drawing or any design or technical information shown thereon. Except for manufacture by vendors of Konami Co., Ltd. and for manufacture under Konami's written license, no right is granted to reproduce, make, have made, use or sell this drawing or the subject matter thereof including, without limitation, the printed circuit board or operating manual relating thereto, whatsoever, unless by written agreement with or written permission from Konami. Copyright 1991 Konami Co., Ltd. All rights reserved.


## CONTROL FOR 1P




## CONTROL FOR 2P



## CONTROL FOR 3P




## CONTROL FOR 4P



- NOTE —
- 1P:NO. 1 PLAYER 2P:NO. 2 PLAYER  
3P:NO. 3 PLAYER 4P:NO. 4 PLAYER
  - SURGE KILLER DIODES FOR COIN COUNTER INSTALLED ON THE P.C.B.
  - YOU CANNOT USE BOTH STEREO AND MONAURAL OUTPUTS AT THE SAME TIME.

GX063  
 PWB 352359C




SPEAKER OUTPUT  
 4P NH CONNECTOR  
 B4P-SHF-1AA J.S.I.  
 CN4

JAMMA 56PIN EDGE CONNECTOR  
 5/32 INCH PITCH

EXTENSION I/O  
 15P NH CONNECTOR  
 B15P-SHF-1AA  
 CN3

EXTENSION I/O  
 15P NH CONNECTOR  
 B15P-SHF-1AA  
 CN4






**PROPRIETARY AND CONFIDENTIAL:**  
 REPRODUCTION OR DISSEMINATION WITHOUT THE SPECIFIC WRITTEN PERMISSION OF KONAMI CO., LTD. IS PROHIBITED. NEITHER KONAMI NOR ITS AFFILIATES, AGENTS, OR CONTRACTORS SHALL BE RESPONSIBLE FOR ANY DAMAGE OR LOSS OF PROFITS OR BUSINESS INTERRUPTIONS RESULTING FROM THE USE OF THIS DRAWING OR ANY INFORMATION CONTAINED HEREIN. THIS DRAWING IS THE PROPERTY OF KONAMI CO., LTD. AND IS LOANED TO YOU FOR YOUR INFORMATION ONLY. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. ANY UNAUTHORIZED REPRODUCTION OR DISSEMINATION OF THIS DRAWING OR ANY INFORMATION CONTAINED HEREIN IS STRICTLY PROHIBITED. FOR MORE INFORMATION, CONTACT KONAMI CO., LTD. AT THE ADDRESS LISTED BELOW.  
 KONAMI CO., LTD.  
 3-1-1 SHIBUYA SCRAMBLE SQUARE, SHIBUYA-KU, TOKYO 100, JAPAN.  
 COPYRIGHT 1991 KONAMI CO., LTD. ALL RIGHTS RESERVED.



KONAMI CO., LTD.

| DRAWING |     | DESIGN    |       | K. FURUKAWA        |                | TITLE        |  | SCHEMATIC |  |
|---------|-----|-----------|-------|--------------------|----------------|--------------|--|-----------|--|
| U27     | U28 | DRAM      | CHECK | K. FURUKAWA        | SUBTITLE       | 04           |  |           |  |
| U29     | U30 | APPROVE   | SCALE | <i>[Signature]</i> | PAGE           |              |  |           |  |
| U31     | U32 | TOLERANCE | DATE  | <i>[Signature]</i> | CODE NO.       | 352995       |  |           |  |
| U33     | U34 |           |       |                    | REG. TYPE      | GX053        |  |           |  |
| U35     | U36 |           |       |                    | SECURITY LEVEL | CONFIDENTIAL |  |           |  |





|           |                    |                |              |
|-----------|--------------------|----------------|--------------|
| DESIGN    | K. FURUKAWA        | TITLE          | SCHEMATIC    |
| DRAW      | K. FURUKAWA        | SUBTITLE       | 05           |
| CHECK     | <i>[Signature]</i> | PAGE           |              |
| APPROVE   | <i>[Signature]</i> | CODE NO.       | 352995       |
| SCALE     |                    | REG. TYPE      | GX063        |
| TOLERANCE |                    | SECURITY LEVEL | CONFIDENTIAL |
| DATE      | 1991/09/18         |                |              |

**DRAWING**

**KONAMI**

KONAMI CO., LTD.

PROPRIETARY AND CONFIDENTIAL: THE SPECIFIC WRITTEN PERMISSION OF KONAMI CO., LTD. 7-3-2, MINATOJIMA-MAKEMACH, CHUO-KU, KOBÉ 650, JAPAN. THIS DRAWING IS ONLY CONDITIONALLY ISSUED. NEITHER REPRODUCTION NOR POSSESSION OF THIS DRAWING OR ANY OPERATING MANUAL RELATING TO KONAMI'S GAMES OR PRODUCTS CONTAINING THIS DRAWING CONFERS OR TRANSFERS ANY RIGHT IN OR LICENSE TO USE THE PRINTED CIRCUIT BOARDS RELATING TO THIS DRAWING OR OTHER SUBJECT MATTER OF THIS DRAWING OR ANY DESIGN OR TECHNICAL INFORMATION SHOWN THEREON, EXCEPT FOR MANUFACTURE BY VENDORS OF KONAMI CO., LTD. AND FOR MANUFACTURE UNDER KONAMI'S WRITTEN LICENSE. NO RIGHT IS GRANTED TO REPRODUCE, MAKE, HAVE MADE, USE OR SELL THIS DRAWING OR THE SUBJECT MATTER THEREOF INCLUDING, WITHOUT LIMITATION, THE PRINTED CIRCUIT BOARD OR OPERATING MANUAL RELATING HERETO, WHATSOEVER, UNLESS BY WRITTEN PERMISSION WITH OR WRITTEN PERMISSION FROM KONAMI.

COPYRIGHT 1991 KONAMI CO., LTD. ALL RIGHTS RESERVED.


|      |        |
|------|--------|
| 014E | COUNT1 |
| 014E | COUNT2 |
| 066E | LEFT   |
| 048E | RED    |
| 048E | GREEN  |
| 048E | BLUE   |
| 048E | SYNC   |

88 CN3 B15P-SHF-1AA  
 88 CN4 B15P-SHF-1AA  
 88 CN1 JAMMA

A B C D E

F

A B C D E F



028E DVCDB



028E DVCDB

**PROPRIETARY AND CONFIDENTIAL:**  
 REPRODUCTION FORBIDDEN WITHOUT THE SPECIFIC WRITTEN PERMISSION OF KONAMI CO., LTD. 7-3-2.  
 HINOKIJIWA-NAKAMACHI, COGHI, JAPAN. THIS DRAWING IS ONLY CONDITIONALLY ISSUED. NEITHER  
 RECEIPT NOR POSSESSION OF THIS DRAWING OR ANY OPERATING MANUAL RELATING TO KONAMI'S GAMES OR PRODUCTS  
 ENTITLES TO THIS DRAWING OR OTHER SUBJECT MATTER OF THE DRAWING OR ANY DESIGN OR TECHNICAL INFORMATION  
 SHOWN THEREON. EXCEPT FOR MANUFACTURE BY VENDORS OF KONAMI CO., LTD. AND FOR MANUFACTURE UNDER  
 KONAMI'S WRITTEN LICENSE, NO RIGHT IS GRANTED TO REPRODUCE, MAKE, HAVE MADE, USE OR SELL THIS DRAWING  
 OR THE SUBJECT MATTER THEREOF, INCLUDING, WITHOUT LIMITATION, THE PRINTED CIRCUIT BOARD OR OPERATING MANUAL  
 RELATING THERETO, WHATSOEVER, UNLESS BY WRITTEN AGREEMENT WITH OR WRITTEN PERMISSION FROM KONAMI.  
 COPYRIGHT 1991, KONAMI CO., LTD. ALL RIGHTS RESERVED.



| DESIGN    | DRAWING   | K. FURUKAWA        | TITLE          | SCHEMATIC    |
|-----------|-----------|--------------------|----------------|--------------|
| DRAW      | CHECK     | K. FURUKAWA        | SUBTITLE       | 07           |
| APPROVE   | APPROVE   | <i>K. Furukawa</i> | PAGE           |              |
| SCALE     | SCALE     | <i>1:1</i>         | CODE NO.       | 352995       |
| TOLERANCE | TOLERANCE |                    | REG. TYPE      | GX063        |
| DATE      | DATE      | 1991/09/18         | SECURITY LEVEL | CONFIDENTIAL |

0 1 2 3 4 5 6 7 8 9



0.1M25CA X22  
330M16E X2

**PROPRIETARY AND CONFIDENTIAL:**  
REPRODUCTION FORBIDDEN WITHOUT THE SPECIFIC WRITTEN PERMISSION OF KONAMI CO., LTD. (7-3-2, MINATOJIMA-NAKAMACHI, CHUO-KU, KOBE 650, JAPAN. THIS DRAWING IS ONLY CONDITIONALLY ISSUED. NEITHER RECEIPT NOR POSSESSION OF THIS DRAWING OR ANY OPERATING MANUAL RELATING TO THE DRAWING OR PRINTED CIRCUIT BOARDS CONTAINING THIS DRAWING CONFERS OR TRANSFERS ANY RIGHT OR INTEREST IN THE DRAWING OR ANY DESIGN OR TECHNICAL INFORMATION RELATING TO THIS DRAWING OR MANUFACTURE BY VENDORS OF KONAMI CO., LTD. AND FOR MANUFACTURE UNDER SHOWN LICENSE. EXCEPT AS SHOWN, NO RIGHT IS GRANTED TO REPRODUCE, MAKE, HAVE MADE, USE OR SELL THIS DRAWING OR THE SUBJECT MATTER THEREOF, INCLUDING, WITHOUT LIMITATION, THE PRINTED CIRCUIT BOARD OR OPERATING MANUAL RELATING THERETO, WHATSOEVER, UNLESS BY WRITTEN AGREEMENT WITH OR WRITTEN PERMISSION FROM KONAMI. COPYRIGHT 1991 KONAMI CO., LTD. ALL RIGHTS RESERVED.



| DESIGN    | K. FURUKAWA      | TITLE          | SCHMATIC     |
|-----------|------------------|----------------|--------------|
| DRAM      | K. FURUKAWA      | SUBTITLE       | 08           |
| CHECK     | <i>Y. Iijima</i> | PAGE           |              |
| APPROVE   | <i>K. Iijima</i> | CODE NO.       | 352995       |
| SCALE     |                  | REG. TYPE      | GX063        |
| TOLERANCE |                  | SECURITY LEVEL | CONFIDENTIAL |
| DATE      | 1991/09/18       |                |              |

**THIS EQUIPMENT COMPLIES WITH THE REQUIREMENTS IN PART 15 OF FCC RULES FOR A CLASS A COMPUTING DEVICE. OPERATION OF THIS EQUIPMENT IN A RESIDENTIAL AREA MAY CAUSE UNACCEPTABLE INTERFERENCE TO RADIO AND TV RECEPTION REQUIRING THE OPERATOR TO TAKE WHATEVER STEPS ARE NECESSARY TO CORRECT THE INTERFERENCE. THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIREED OPERATION.**



900 Deerfield Parkway, Buffalo Grove, 60089-4510  
Telephone: (708) 215-5100, Telex: 6871385 KONAM UW, Fax: (708) 215-5122